

motion servo drive, Lexium 28, single and three phase, 200 to 240V, 1kW

LXM28AU10M3X

Main

Range of product	Lexium 28
Device short name	LXM28A
Product or component type	Motion servo drive
Format of the drive	Compact housing
Line current	8.5 A 176.3 % at 220 V, single phase 8.5 A 155.5 % at 220 V, three phase

Complementary

Network number of phases	Single phase Three phase
[Us] rated supply voltage	200240 V (- 1015 %) for three phase 200240 V (- 2015 %) for single phase
Supply voltage limits	200255 V three phase 170255 V single phase
Supply frequency	50/60 Hz - 55 %
Network frequency	47.563 Hz
EMC filter	Without EMC filter
Continuous output current	7 A at 16 kHz
Output current 3s peak	21 A at 220 V
Continuous power	1000 W at 220 V
Nominal power	1 kW at 220 V 16 kHz
Switching frequency	16 kHz
Overvoltage category	III
Maximum leakage current	4.5 mA
Output voltage	<= power supply voltage
Electrical isolation	Between power and control
Type of cable	Shielded motor cable (temperature: 055 °C) copper
Electrical connection	Spring terminal, clamping capacity: 1.31.5 mm², AWG 16 (L1-L2) Spring terminal, clamping capacity: 1.31.5 mm², AWG 16 (R, S, T) Spring terminal, clamping capacity: 1.31.5 mm², AWG 16 (U, V, W, PE) Spring terminal, clamping capacity: 1.31.5 mm², AWG 16 (PA/+, PBe)
Discrete input number	8 programmable (CN1) 1 pulse train input (PTI) (CN1) 2 fast capture (CN1) 1 safety function STO (CN9)
Discrete input voltage	24 V DC for logic

Discrete input logic	Positive or negative (CN1)
Discrete output number	5 logic output (CN1) at 1224 V DC 1 pulse train output (PTO) (CN1)
Discrete output voltage	1224 V DC
Discrete output logic	Positive or negative (CN1)
Analogue input number	2
Absolute accuracy error	0.1 %
Analogue input type	V_REF voltage analog input: - 1010 V, impedance: 10 kOhm, resolution: 14 bits T_REF voltage analog input
Control signal type	Servo motor encoder feedback CN2
Protection type	Against reverse polarity: inputs signal Against short-circuits: outputs signal Overcurrent: motor Overvoltage: motor Undervoltage: motor Overheating: motor Overload: motor Overspeed: motor
Safety function	STO (safe torque off), integrated
Safety level	SIL 2 conforming to IEC 61800-5-2: 2007 SIL 2 conforming to IEC 61508-1: 2010 PL d/category 3 conforming to ISO 13849-1: 2008 SIL 2 conforming to ISO 13849-1: 2009/AC SIL 2 conforming to IEC 60204-1: 2006 SIL 2 conforming to IEC 60204-1: 2009/A1 SIL 2 conforming to IEC 60204-1: 2010/AC SIL 2 conforming to IEC 60204-1: 2010/AC SIL 2 conforming to IEC 62061: 2012
Communication interface	CANopen, integrated CANmotion, integrated
Connector type	RJ45 (CN4) for CANopen, CANmotion
Method of access	Slave
Transmission rate	250 kbit/s for bus length of 100250 m for CANopen, CANmotion 500 kbit/s for bus length of 4100 m for CANopen, CANmotion 1 Mbit/s for bus length of 4 m for CANopen, CANmotion
Number of addresses	1127 for CANopen, CANmotion
Physical interface	RS485 for Modbus Serial line slave
Status LED	1 LED (red) charge 1 LED (green) RUN 1 LED (red) error
Signalling function	Servo status and fault codes five 7-segment display units
Marking	CE CULus CSA
type of cooling	Integrated fan
Operating position	Vertical
Product compatibility	Servo motor BCH2 (130 mm, 1 motor stacks) at 1000 W Servo motor BCH2 (100 mm, 1 motor stacks) at 1000 W Servo motor BCH2 (130 mm, 2 motor stacks) at 900 W Servo motor BCH2 (130 mm, 4 motor stacks) at 850 W
Width	55 mm
Height	150 mm
Depth	170 mm
Product weight	1.2 kg

Supply voltage description	Three phase 220 V AC 5060 Hz Single phase 220 V AC 5060 Hz
Network number of phases	3 1
Drive voltage drop coefficient	1
Field weakening	False
Continuous output current 2	7 A
Output current 3s peak 2	21 A at 220 V
Switching frequency 2	16 kHz
Continuous output current 3	7 A
Output current 3s peak 3	21 A at 220 V
Switching frequency 3	16 kHz
communication interface	CANmotion Pulse train output CANopen DS402 Pulse train input
Emc filter compatibility	Type 021 Type 022

Environment

Conducted emission - test level: level 3 category C3 conforming to IEC 61800-3	
IEC 61800-5-1	
CE	
CSA	
cULus	
IP20	
3M4 amplitude = 3 mm (f = 9200 Hz) conforming to IEC 60721-3-3	
10 gn, type I conforming to IEC 60721-3-3	
595 % without condensation	
055 °C	
-2565 °C	
<= 1000 m without derating	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.500 cm
Package 1 Width	23.000 cm
Package 1 Length	23.500 cm
Package 1 Weight	1.499 kg
Unit Type of Package 2	S03
Number of Units in Package 2	5
Package 2 Height	30.000 cm
Package 2 Width	30.000 cm

Package 2 Length	40.000 cm
Package 2 Weight	7.990 kg



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

☑ Environmental footprint	
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	2591
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances	
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
REACh Regulation	REACh Declaration
PVC free	Yes

Use Again

○ Repack and remanufacture	
Circularity Profile	End of Life Information
Take-back	No


Product datasheet

LXM28AU10M3X

Dimensions Drawings

Dimensions

Dimensions of Drive



LXM28AU10M3X

Mounting and Clearance

Mounting Clearance

Mounting Distances and Air Circulation

mm ŵa

